Suite 2500 300 South Wacker Drive Chicago, Illinois 60606 Telephone (312) 360-0080 Facsimile (312) 360-9315

GREER, BURNS & CRAIN, LTD.

Facsimile Cover Sheet

To:	Examiner Martinez	From:	Joseph Fox
Fax:	(571) 273-4152	Date:	September 1, 2006
Your Ref:	Serial No. 10/767,426	Our Ref;	3408.69382
9 Pages (including cover sheet)		Original Will [☐ Will Not ⊠ Follow
Urgent		⊠For Review	☐Please Reply
IF THIS FAC: 360-0080.	SIMILE IS RECEIVED IN	COMPLETE, PLEASE	CONTACT Elizabeth Crossin AT (312)
• Comments:			

The documents accompanying this facsimile transmission contain information that may be confidential or privileged and exempt from disclosure under applicable law. The information is intended to be for the use of the individual or entity named on this transmission sheet. If you are not the intended recipient, be aware that any disclosure, copying, distribution or use of the contents of this information is without authorization and is prohibited. If you have received this facsimile in error, please notify us by collect telephone immediately so that we can arrange for the retrieval of the original documents at no cost to you.

Proposed Amendment

APPENDIX

data ofstored in a logical unit, which is concatenation unit having a plurality of logical units, each logical unit being comprised of a single one or a plurality of more physical units, by a request from a host, comprising:

- a channel adapter for interfacing with said host; and
- a plurality of controllers which control each one of the plurality of logical units,

wherein when said channel adapter receives an I/Osaid request to a concatenation logical unit concatenating a plurality of said logical units from said host, said channel adapter sends an I/O data request for one logical unit of said plurality of logical units to onea first controller which causes said one logical unit constituting said concatenation logical unit, out of said plurality of controllers, to execute the I/O processing in said one first controller, and then said channel adapter sends another I/O data request for another logical unit of said plurality of logical units to another a second controller which causes said another logical unit constituting said concatenation logical unit, out of said plurality of controllers, to execute the I/O processing in said other controller second controller, and

wherein said first controller judges whether said I/O data request is an I/O request extending over to said second controller which is in charge of said another logical

unit after said I/O processing in said first controller, and sends a message indicative of the judgment result to said channel adapter.

2. (Cancelled)

3. (Currently Amended) The storage control apparatus according to Claim 2,1, wherein said-each controller has a table for storing the logical block address range of each logical unit, and

said <u>first</u> controller refers to said table in the logical block address range requested by said I/O <u>data</u> request, and judges whether said I/O <u>data</u> request is an I/O <u>data</u> request extending over to said <u>anothersecond</u> controller, which is in charge of said another logical <u>unit constituting said concatenation logical</u> unit.

- 4. (Currently Amended) The storage control apparatus according to Claim 2,1, wherein said channel adapter sends said I/O data request to said another second controller according to the response from said enefirst controller that the I/O data request extends to said another second controller.
- (5.) (Currently Amended) The storage control apparatus according to Claim 1, A storage control apparatus for accessing data stored in a concatenation unit

having a plurality of logical units, each logical unit being comprised of one or more physical units, by a request from a host, comprising:

a channel adapter for interfacing with said host; and

a plurality of controllers which control each one of the plurality of logical units,

wherein when said channel adapter receives said request from said host, said channel adapter sends an I/O data request for one logical unit of said plurality of logical units to a first controller which causes said one logical unit to execute I/O processing in said first controller, and then said channel adapter sends another I/O data request for another logical unit of said plurality of logical units to a second controller which causes said another logical unit to execute I/O processing in said second controller,

wherein said channel adapter has a table for storing said controllers corresponding to each logical unit, the logical block address range of each logical unit, and the logical units constituting said concatenation logical-unit, and

said channel adapter selects a controller of said corresponding logical unit when an I/Osaid request is received from said host.

6. (Currently Amended) The storage control apparatus according to Claim 5, wherein said each controller has a table for storing the logical block address range of each logical unit, and

said first controller refers to said table in the logical block address range requested by said I/O data request, and judges whether said I/O data request is an I/O data request extending over to said anothersecond controller, which is in charge of said another logical unit constituting said concatenation logical unit.

- 7. (Currently Amended) The storage control apparatus according to Claim 1, wherein said each controller comprises:
- a cache memory for storing a part of the data of said logical unit which the controller is in charge of; and
- a processing unit for executing I/O processing using said cache memory according to said I/O data request.
- 8. The storage control apparatus according to Claim 1, (Original) wherein said channel adapter is constituted by a plurality of channel adapters for connecting said plurality of controllers.
- A storage control method for accessing (Currently Amended) data ofstored in a logical concatenation unit, which is each logical unit being comprised of a singleone or a plurality of more physical units, by a request from a host, comprising steps of:

receiving an LOsaid request from said host to a concatenation logical unit concatenating a plurality of logical-units by a channel adapter;

sending an I/O data request for one logical unit of said plurality of logical units from said channel adapter to onea first controller which is in charge of said one logical unit constituting-said concatenation logical unit-out of a plurality of controllers which is are in charge of said plurality of logical units;

executing I/O processing in said one first controller;

judging whether said I/O data request is an I/O data request extending over to said second controller which is in charge of said another logical unit after said I/O processing by said first controller;

sending a message indicative of the judgment result to said channel adapter.

I/O data request for another logical unit of said plurality of logical units from said channel adapter to anothera second controller which is in charge of said another logical unit constituting said concatenation-logical unit out of aof said plurality of controllers which is are in charge of said plurality of logical units; and executing the-I/O processing in said other controller.second controller.

10. (Cancelled)

11. (Currently Amended) The storage control method according to Claim 10,9, wherein said response step comprises:

a step of referring to a table storing the logical block address range of each logical unit in the logical block address range requested by said I/O data request by said one first controller; and

a step of judging whether said I/O data_request is an I/O data_request extending over to said another second controller, which is in charge of said another logical unit constituting said concatenation logical unit.

12. (Currently Amended) The storage control method according to Claim 10,9, wherein the step of executing I/O processing in said another second controller further comprises a step of sending said I/O data request to said another second controller according to the response from said one first controller that the I/O data request extends to said other second controller by said channel adapter.

Claim 9, A storage control method for accessing data stored in a concatenation unit, each logical unit being comprised of one or more physical units, by a request from a host, comprising steps of:

receiving said request from said host to a channel adapter;

sending an I/O data request for one logical unit of said plurality of logical units from said channel adapter to a first controller which is in charge of said one logical unit out of a plurality of controllers which are in charge of said plurality of logical units:

executing I/O processing in said first controller;

sending another I/O data request for another logical unit of said plurality of logical units from said channel adapter to a second controller which is in charge of said another logical unit of said plurality of controllers which are in charge of said plurality of logical units; and

executing I/O processing in said second controller,

wherein said reception step comprises:

a step of referring to a table for storing said controllers corresponding to each logical unit, logical block address range of each logical unit, and logical units constituting said concatenation logical unit by said channel adapter; and

a step of selecting a controller of said corresponding logical unit when an L'Osaid request is received from said host.

14. (Currently Amended) The storage control method according to Claim 13, wherein said response step comprises:

a step of referring to a table storing the logical block address range of each logical unit in the logical block address range requested by said I/O data request by said onefirst controller; and

a step of judging whether said I/O data request is an I/O data request extending over to another said second controller, which is in charge of another logical unit constituting said concatenation logical unit.

- 15. (Currently Amended) The storage control method according to Claim 9, wherein the I/O processing step for said I/O <u>data</u> request further comprises a step of executing I/O processing using a cache memory for storing a part of the data of said logical unit which each controller controls according to said I/O <u>data</u> request.
- 16. (Original) The storage control method according to Claim 9, wherein said channel adapter is constituted by a plurality of channel adapters for connecting said plurality of controllers, and said reception step further comprises a step of which one of the plurality of channel adapters for connecting said plurality of controllers receives the I/O request from said host.